



VENEZIA 2



Venezia 2	Comp. sem laterais Länge ohne Seiten Longeur sans joues Longitud sin laterales Длина без боковин	Modelo Model Modell Modelo Modelo Модель			Temp. de funcionamento Working temperature Betriebstemperatur Temp. de fonctionnement Temperatura de trabajo Рабочая температура	Superfície de exposição horizontal Horizontal display surface Gesamte Ausstellefläche Surface d'exposition horizontale Superficie de exposición de apoyo Горизонтальная площадь экспозиции	Capacidade útil Net volume Nutzleistung Capacité utile Capacidad útil Полезный объём	
		REMOTO REMOTE		+ UCE WITH UNIT			vetrina display surface	cella storage
		carenato closed	con zamponi on feet	carenato closed				
		mm						°C
VCA con riserva with storage	1250	•	•	•	0°C / +2°C +2°C / +4°C	1,1	143	131
	1875	•	•	•		1,6	214	197
	2500	•	•	•		2,2	286	263
	3750	•	•	•		3,3	428	394
VCB con riserva with storage	1250	•	•	•		1,1	143	131
	1875	-	-	-		1,6	214	197
	2500	•	•	•		2,2	286	263
	3750	•	•	•		3,3	428	394
SELF con riserva with storage	1250	•	•	•		1,1	143	131
	1875	•	•	•		1,6	214	197
	2500	•	•	•		2,2	286	263
	3750	•	•	•		3,3	428	394
VCA MAXI	1250	•	•	•		1,1	283	
	1875	•	•	•		1,6	425	
	2500	•	•	•		2,2	567	
	3750	•	•	•		3,3	850	
VCB MAXI	1250	•	•	•	1,1	283		
	1875	•	•	•	1,6	425		
	2500	•	•	•	2,2	567		
	3750	•	•	•	3,3	850		
SELF MAXI	1250	•	•	•	1,1	283		
	1875	•	•	•	1,6	425		
	2500	•	•	•	2,2	567		
	3750	•	•	•	3,3	850		
VCA FISH	937	•	•	•	+2°C / +4°C	0,7	60	
	1250	•	•	•		1,0	80	
	1875	•	•	•		1,5	120	
	2500	•	•	•		2,0	160	
	3125	•	•	•		2,5	200	
	3750	•	•	•		3,0	240	
VCB FISH	937	•	•	•		0,7	60	
	1250	•	•	•		1,0	80	
	1875	•	•	•		1,5	120	
	2500	•	•	•		2,0	160	
	3125	•	•	•		2,5	200	
	3750	•	•	•		3,0	240	
SELF FISH	937	•	•	•		0,7	60	
	1250	•	•	•		1,0	80	
	1875	•	•	•		1,5	120	
	2500	•	•	•		2,0	160	
	3125	•	•	•		2,5	200	
	3750	•	•	•		3,0	240	

Venezia 2	Comp. sem laterais Länge ohne Seiten Longeur sans joues Longitud sin laterales Длина без боковин	Modelo Model Modell Modele Modelo Модель			Temp. de funcionamento Working temperature Betriebstemperatur Temp. de fonctionnement Temperatura de trabajo Рабочая температура	Superficie de exposição horizontal Horizontal displaysurface Gesamte Ausstellungsfläche Surface d'exposition horizontale Superficie de exposición de arroyo Горизонтальная площадь экспозиции	Capacidade útil Net volume Nutzleistung Capacité utile Capacidad útil Полезный объем				
		REMOTO REMOTE		+ UCE WITH UNIT			vetrina display surface	cella storage			
		carenado closed	con zamponi on feet	carenado closed							
		mm					°C	m ²	dm ³		
VCA BT	1250	•	•	•	-18°C / -25°C	1,0	320				
	1875	•	•	•		1,6	480				
	2500	•	•	-		2,0	640				
VCA TCBM	937	•	•	-	+65°C	0,8	80				
	1250	•	•	-		1,0					
VCB TCBM	937	•	•	-		0,8					
	1250	•	•	-		1,0					
VCA TCPW	937	•	•	-		0,8					
	1250	•	•	-		1,0					
VCB TCPW	937	•	•	-		0,8					
	1250	•	•	-		1,0					
H125	1250	•	•	•		0°C / +2°C +2°C / +4°C			1,55	420	
	2500	•	•	•					3,10	840	
	3750	•	•	•	4,65		1260				
H150	1250	•	•	•	2,17		550				
	2500	•	•	•	4,34		1100				
	3750	•	•	•	6,51		1650				
VDA con riserva with storage	1250	•	•	•	0°C / +2°C +2°C / +4°C	1,1	143	131			
	1875	•	•	•		1,6	214	197			
	2500	•	•	•		2,2	286	263			
	3750	•	•	•		3,3	428	394			
VDB con riserva with storage	1250	•	•	•		1,1	143	131			
	1875	•	•	•		1,6	214	197			
	2500	•	•	•		2,2	286	263			
	3750	•	•	•		3,3	428	394			
VDB SELF con riserva with storage	1250	•	•	•		1,1	143	131			
	1875	•	•	•		1,6	214	197			
	2500	•	•	•		2,2	286	263			
	3750	•	•	•		3,3	428	394			
VDA MAXI	1250	•	•	•		1,1	283				
	1875	•	•	•		1,6	425				
	2500	•	•	•		2,2	567				
	3750	•	•	•		3,3	850				
VDB MAXI	1250	•	•	•		1,1	283				
	1875	•	•	•		1,6	425				
	2500	•	•	•		2,2	567				
	3750	•	•	•		3,3	850				

Venezia 2	Comp. sem laterais Länge ohne Seiten Longeur sans joues Longitud sin laterales Длина без боковин	Modelo Model Modell Modele Modelo Модель			Temp. de funcionamento Working temperature Betriebstemperatur Temp. de fonctionnement Temperatura de trabajo Рабочая температура	Superfície de exposição horizontal Horizontal display surface Gesamte Ausstellungsfläche Surface d'exposition horizontale Superficie de exposición de apoyo Горизонтальная площадь экспозиции	Capacidade útil Net volume Nutzleistung Capacité utile Capacidad útil Полезный объем		
		REMOTO REMOTE		+ UCE WITH UNIT			vetrina display surface	cella storage	
		carenado closed	con zamponi on feet	carenado closed					
		mm					°C	m ²	dm ³
VDA FISH	937	•	•	•	+2°C / +4°C	0,7	60		
	1250	•	•	•		1,0	80		
	1875	•	•	•		1,5	120		
	2500	•	•	•		2,0	160		
	3125	•	•	•		2,5	200		
	3750	•	•	•		3,0	240		
VDB FISH	937	•	•	•		0,7	60		
	1250	•	•	•		1,0	80		
	1875	•	•	•		1,5	120		
	2500	•	•	•		2,0	160		
	3125	•	•	•		2,5	200		
	3750	•	•	•		3,0	240		
VDB SELF FISH	937	•	•	•		0,7	60		
	1250	•	•	•		1,0	80		
	1875	•	•	•		1,5	120		
	2500	•	•	•		2,0	160		
	3125	•	•	•		2,5	200		
	3750	•	•	•		3,0	240		
VDA BT	1250	•	•	•		-18°C / -25°C	1,0	320	
	1875	•	•	•			1,6	480	
	2500	•	•	-			2,0	640	
VDA TCBM	937	•	•	-		+65°C	0,8	80	
	1250	•	•	-			1,0		
VDB TCBM	937	•	•	-			0,8		
	1250	•	•	-	1,0				
VDA TCPW	937	•	•	-	0,8				
	1250	•	•	-	1,0				
VDB TCPW	937	•	•	-	0,8				
	1250	•	•	-	1,0				
H125 VD	1250	•	•	•	0°C / +2°C +2°C / +4°C		1,55		420
	2500	•	•	•			3,10		840
	3750	•	•	•		4,65	1260		
H150 VD	1250	•	•	•		2,17	550		
	2500	•	•	•		4,34	1100		
	3750	•	•	•		6,51	1650		

• DISPONÍVEL - AVAILABLE

- NÃO DISPONÍVEL - NOT AVAILABLE